

SUPERDOME TIRE RING DRUM



Bent Manufacturing Company

SUPERDOME TIRE RING DRUM

FEATURES:

- Double (one on each side) flag mount holes with pre-molded stops for all-purpose flagging situations.
- Enlarged arch carry handle allows gloved workers easy, comfortable and secure grip.
- Ribbed dome top for increased target value and superior structural strength.
- Recessed reflective band tiers, maximum width 6". Accommodates USA M.U.T.C.D. 2" maximum spacing specifications.
- Two pre-molded light mounts are designed for standard size bolt and cup washers.
- Rounded dome top discourages any dangerous debris or rocks to collect on top of drum.
- Allows for tire ring ballast as a base.
- Tested and certified to meet the crashworthy requirements of NCHRP-350.

SPECIFICATIONS:

Drum Materials	Low or High Density Polyethylene
Color	Cad. Orange
Drum Weight	8.5 Pounds
Drum Height	Base of drum to bottom of dome – 36" (meets Fed. M.U.T.C.D. VI, Section 6F-5e.) Base of drum to top of dome – 39"/Base of drum to top of handle – 41.5"
Drum Diameter	18" minimum (meets Fed. M.U.T.C.D. Part VI, Section 6F-5e.)
Reflectivity	Engineer Grade, High Intensity, Diamond Grade
Reflective Band Size	4"/6"
Light Brackets	2 each
Flag Brackets	2 each
Base Option	Tire Ring Ballast
Base Weight	22-26#

Bent Manufacturing Company, Inc

17311 Nichols Street

Huntington Beach, CA 92647-5721

(714) 842-0600 • FAX (714) 842-2959

(888) 842-0600 • FAX (888) 842-2368

E-Mail: bmc@bentmfg.com

Http://www.bentmfg.com